

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
17 March 2005 (17.03.2005)

PCT

(10) International Publication Number
WO 2005/023912 A3

(51) International Patent Classification⁷: C08J 5/18,
C08L 23/08

(21) International Application Number:
PCT/US2004/029124

(22) International Filing Date:
3 September 2004 (03.09.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/500,585 5 September 2003 (05.09.2003) US

(71) Applicant (for all designated States except US): DOW
GLOBAL TECHNOLOGIES, INC. [US/US]; Washington Street,
1790 Building, Midland, MI 48674 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): OSWALD, Thomas,
T. [GB/US]; 323 Huckleberry, Lake Jackson, TX 77566
(US). COOPER, James, L. [US/US]; 54 Yaupon Court,
Lake Jackson, TX 77566 (US). WEINHOLD, Jeffrey
[US/US]; 510 That Way Apt. 510, Lake Jackson, TX
77566 (US). GILLESPIE, David, T. [US/US]; 2710 West
Oaks Boulevard, Pearland, TX 77584 (US).

(74) Agent: HOPPE, James, T.; The Dow Chemical Company,
Intellectual Property, P.O. Box 1967, Midland, MI 48641-
1967 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

(88) Date of publication of the international search report:
11 August 2005

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

WO 2005/023912 A3

(54) Title: IMPROVED RESIN COMPOSITIONS FOR EXTRUSION COATING

(57) Abstract: A composition is disclosed which is particularly suited for use in extrusion coating. The composition comprises a polymeric material having a rheology such that the slope S of a natural log-natural log plot of loss modulus (or G') versus storage modulus (or G') is greater than $[0.635^*(\text{melt index})+13.2]/[(\text{melt index})+16.6]$, and wherein the polymeric material has a CDF RI fraction less than 0.23 of a GPC chromatogram which has a molecular weight above 85,000 g/mol, and a CDF LS fraction of more than 0.07 at a conventional GPC molecular weight of 1,750,000 g/mol or greater. The compositions exhibit reduced neck-in when used in extrusion coating and the neck-in is independent of melt strength, thereby facilitating improved extrusion processes.